

(4) From 100 MHz to 8 GHz, use radiated susceptibility tests at a minimum of 5 V/m.

[Doc. No. FAA-2006-23657, 72 FR 44027, Aug. 6, 2007]

## PART 29—AIRWORTHINESS STANDARDS: TRANSPORT CATEGORY ROTORCRAFT

### Subpart A—General

- Sec.  
29.1 Applicability.  
29.2 Special retroactive requirements.

### Subpart B—Flight

#### GENERAL

- 29.21 Proof of compliance.  
29.25 Weight limits.  
29.27 Center of gravity limits.  
29.29 Empty weight and corresponding center of gravity.  
29.31 Removable ballast.  
29.33 Main rotor speed and pitch limits.

#### PERFORMANCE

- 29.45 General.  
29.49 Performance at minimum operating speed.  
29.51 Takeoff data: general.  
29.53 Takeoff: Category A.  
29.55 Takeoff decision point (TDP): Category A.  
29.59 Takeoff path: Category A.  
29.60 Elevated heliport takeoff path: Category A.  
29.61 Takeoff distance: Category A.  
29.62 Rejected takeoff: Category A.  
29.63 Takeoff: Category B.  
29.64 Climb: General.  
29.65 Climb: All engines operating.  
29.67 Climb: One engine inoperative (OEI).  
29.71 Helicopter angle of glide: Category B.  
29.75 Landing: General.  
29.77 Landing Decision Point (LDP): Category A.  
29.79 Landing: Category A.  
29.81 Landing distance: Category A.  
29.83 Landing: Category B.  
29.85 Balked landing: Category A.  
29.87 Height-velocity envelope.

#### FLIGHT CHARACTERISTICS

- 29.141 General.  
29.143 Controllability and maneuverability.  
29.151 Flight controls.  
29.161 Trim control.  
29.171 Stability: general.  
29.173 Static longitudinal stability.  
29.175 Demonstration of static longitudinal stability.  
29.177 Static directional stability.  
29.181 Dynamic stability: Category A rotorcraft.

### GROUND AND WATER HANDLING CHARACTERISTICS

- 29.231 General.  
29.235 Taxiing condition.  
29.239 Spray characteristics.  
29.241 Ground resonance.

### MISCELLANEOUS FLIGHT REQUIREMENTS

- 29.251 Vibration.

### Subpart C—Strength Requirements

#### GENERAL

- 29.301 Loads.  
29.303 Factor of safety.  
29.305 Strength and deformation.  
29.307 Proof of structure.  
29.309 Design limitations.

#### FLIGHT LOADS

- 29.321 General.  
29.337 Limit maneuvering load factor.  
29.339 Resultant limit maneuvering loads.  
29.341 Gust loads.  
29.351 Yawing conditions.  
29.361 Engine torque.

#### CONTROL SURFACE AND SYSTEM LOADS

- 29.391 General.  
29.395 Control system.  
29.397 Limit pilot forces and torques.  
29.399 Dual control system.  
29.411 Ground clearance: tail rotor guard.  
29.427 Unsymmetrical loads.

#### GROUND LOADS

- 29.471 General.  
29.473 Ground loading conditions and assumptions.  
29.475 Tires and shock absorbers.  
29.477 Landing gear arrangement.  
29.479 Level landing conditions.  
29.481 Tail-down landing conditions.  
29.483 One-wheel landing conditions.  
29.485 Lateral drift landing conditions.  
29.493 Braked roll conditions.  
29.497 Ground loading conditions: landing gear with tail wheels.  
29.501 Ground loading conditions: landing gear with skids.  
29.505 Ski landing conditions.  
29.511 Ground load: unsymmetrical loads on multiple-wheel units.

#### WATER LOADS

- 29.519 Hull type rotorcraft: Water-based and amphibian.  
29.521 Float landing conditions.

#### MAIN COMPONENT REQUIREMENTS

- 29.547 Main and tail rotor structure.  
29.549 Fuselage and rotor pylon structures.  
29.551 Auxiliary lifting surfaces.